

Micro Ohm Meter 200 A

Micro
Centurion

Fully Automatic

5 Ranges for Precision and Accuracy

Pure filtered DC Output




Raytech
SWITZERLAND

M-Series

Micro Ohm Meter 200 A

Micro Centurion II

Features

Automatic measurements from 0.00 $\mu\Omega$... 5 Ω
Pure filtered DC power source
Highest accuracy readings
Microprocessor based system
Internal storage for test results
Large LCD display with back light
Single or continuous measurements
Automatic data storage
Fully remote operation and control with an external PC
Automatic shut off for over-temperature condition
Automatic calibration system and system diagnostics
Centronics (parallel) Interface & RS232 (serial) interface
Extremely rugged (can withstand a drop test of 1 meter)
User defined „Current on“-Ramp
Internal panel mount printer

Measurement Parameters

Current Range	Measuring Range	Accuracy	Resolution
200 A	0.00 $\mu\Omega$... 20 m Ω	$\pm 0.1\%$ Rdg $\pm 0.01\mu\Omega$	5 Digits or 0.01 $\mu\Omega$
100 A	0.00 $\mu\Omega$... 40 m Ω	$\pm 0.1\%$ Rdg $\pm 0.02\mu\Omega$	5 Digits or 0.02 $\mu\Omega$
50 A	0.00 $\mu\Omega$... 100 m Ω	$\pm 0.1\%$ Rdg $\pm 0.04\mu\Omega$	5 Digits or 0.05 $\mu\Omega$
20 A	0.0 $\mu\Omega$... 1.0 Ω	$\pm 0.1\%$ Rdg $\pm 0.1\text{ m}\Omega$	5 Digits or 0.1 $\mu\Omega$
10 A	0.0 $\mu\Omega$... 5.0 Ω	$\pm 0.1\%$ Rdg $\pm 0.2\text{ m}\Omega$	5 Digits or 0.2 $\mu\Omega$

Resistance Range 0.00 $\mu\Omega$ to 5 Ω
Measuring duty cycle 200 A 10 min. on, 2 min off. 100 A & below continuous
Temperature Operating -10 °C to 60 °C, Storage -20 °C to 70 °C

Specifications

Model	Micro Centurion II
Size	L: 521 mm (20.5") W: 432 mm (17") H: 216 mm (8.5")
Weight	14.4 kg (31.5 lbs.)
Input Power	100 to 250 Vac (1.1 kW max.), 50/60 Hz, auto ranging
Output Power	1000 Watt
Test Current	User Selectable: 200, 100, 50, 20, 10 A DC
Panel Display	LCD Graphic with back light
Front Panel	Sealed, Anodized with a multi-actuation rotary knob
Interface	9 Pin RS232 serial / 25 Pin Centronics parallel
Memory Storage	Internally stores up to 2000 complete test results

Accessories

Current and voltage lead set 5 meters, instruction manual, software for data download

Options

MCO 101	200A Kelvin clip set
TP 01	External temperature probe



Raytech GmbH

Oberebenestrasse 11 Tel. +41 56 648 60 10 welcome@raytech.ch
CH-5620 Bremgarten Fax +41 56 648 60 11 www.raytech.ch